

Health Care Engineers and Fire Safety

Minnesota Health Care Engineers Association
Spring Conference
May 2, 2008

Patrick Sheehan, Supervisor, Health Care Fire Inspections
Gary Schroeder, Health Care Fire Inspector
Kurt Kastella, Health Care Fire Inspector
Minnesota State Fire Marshal Division

This presentation will focus on what and how health care facility engineers should approach the reoccurring testing, preventive maintenance and documentation requirements for fire safety systems.

Code References


- NFPA 10 – Portable Fire Extinguishers
- NFPA 13 – Installation of Sprinkler Systems
- NFPA 20 – Fire Pump Installation
- NFPA 25 – Inspection, Testing, Maintenance of Water Base System
- NFPA 72 – National Fire Alarm Code
- NFPA 96 – Commercial Cooking Operations
- NFPA 99 – Standard for Healthcare Facilities
- **NFPA 101 – Life Safety Code (2000)**
- NFPA 110 – Standard for Emergency Standby Power Systems

If you didn't document it.

It didn't happen!

**Annual Test
Dates Should Not
Be More Than
365 Days Apart**

Fire Life Safety Documentation



- 3 ring binder – Min. 4”
- Index Dividers – Min. 17
- Make sure the management staff, facility maintenance staff know where this book it kept

Index Dividers – Tab 1

- Current building floor plan
- Building year (each addition)
- Construction type (each addition)

Index Dividers – Tab 2

- Facility emergency plan (K048)
 - You may place plan here or indicate where a current plan can be found

2000 NFPA 101 - 18.7.1.1, 19.7.1.1

Index Dividers – Tab 2

- Staff properly trained in emergency procedures (K050)
 - You may place the in-service records here or indicate where the in-service records can be found
 - 2000 NFPA 101 – 18.7.2.3, 19.7.2.3

Index Dividers – Tab 3

- Smoking policy (K066)
 - Smoking regulations shall be adopted and shall include not less than the following provisions:
 - 2000 101 - 18.7.4, 19.7.4

Index Dividers – Tab 4

- Fire Drills – once per quarter per shift and drills held at varying times (K050)
 - You may place the fire drill records here or indicate where the fire drill records can be found
 - 2000 NFPA 101 – 18.7.1.2, 19.7.1.2

Index Dividers – Tab 5

- Out of service policy (fire watch) for fire sprinkler and fire alarm systems outages for more than 4 hours in 24 hour period. (K154 & K155)
- Make sure the DSFM inspector name and phone numbers is included
 - 2000 NFPA 101 – 9.6.1.8 , 9.7.6.1

Index Dividers – Tab 6

- Fire alarm system
 - Annual testing report (K052) see 1999 NFPA 72 – 7-5.2.2 and figure 7-5.2.2
- D.A.C.T monthly testing (K052)
 - You can record this on your fire drill report
 - Have a separate record
 - 2000 NFPA 101 – 9.6.1.4 and 1999 NFPA 72 7-3.2.1

Index Dividers – Tab 7

– Smoke detector sensitivity testing (K052)

- Must show the sensitivity range (low and high range), and the actual tested sensitivity for each smoke detector, and test date(s).
- 2000 NFPA 101 – 9.6.1.4 and 1999 NFPA 72 7-3.2.1

Index Dividers – Tab 8

- Resident room smoke alarm (single station) weekly or monthly testing per manufacturer instruction (K054)

Index Dividers – Tab 9

- Fire sprinkler system (K056 – K062)
 - Annual test / inspection
 - Quarterly flow alarm test
 - Fire pump – Weekly and annual
- 2000 NFPA 101 - 18.7.6, 19.7.6, 4.6.12,
1999 NFPA 13, and 1998 NFPA 25

Index Dividers – Tab 10

- Range hood system (K069)
 - 6 month inspection report
 - Make sure system activates the building fire alarm system

- 2000 NFPA 101 - 9.2.3., 18.3.2.6, 19.3.2.6, 1998 NFPA 96

Index Dividers – Tab 11

- Portable fire extinguishers (K064)
 - Monthly in-house inspection
 - Annual vendor service date
 - 6 year maintenance date
 - 12 year Hydrostatic test date
- 2000 NFPA 101 - 9.7.4.1, 18.3.5.6, 19.3.5.6
- 1998 NFPA 10

Index Dividers – Tab 12

- Generator (K144)
 - Weekly visual
 - Monthly 30 minute load test
- 1999 NFPA 99, 3.4.4.1, 1999 NFPA 110, 8.4.2

Index Dividers – Tab 13

- Battery operated emergency lights and exit signage (K046)
 - Monthly (30 seconds)
 - Yearly (90 minutes)

- 2000 NFPA 101 - 7.9., 18.2.9.1, 19.2.9.1.

Index Dividers – Tab 14

- Fire/Smoke Damper (K067)
 - Visually inspected / tested every 4 years
 - 2000 NFPA 101 – 9.2, 18.5.2.1, 19.5.2.1,, 18.5.2.2, 19.5.2.2, and 1999 NFPA 90A

Index Dividers – Tab 15

- Flame spread documentation
 - Drape and curtains (K074)
 - Interior walls, ceiling, and floor finishes (K014, K015, and K016)
 - Decorations (K073)

- 2000 NFPA 101 – Chapter 18 - 19

Index Dividers – Tab 16

- Upholstered furniture flammability
 - Newly introduce upholstered furniture (K074)
Since March 2003
 - California technical bulletin 133 or 117, NFPA 266

Index Dividers – Tab 17



- Laboratory
 - Procedure policy reviewed annually
(K131) 1999 NFPA 99 - 10.2.1.3.2
 - Incident reviewed monthly
(K132) 1999 NFPA 99 - 10.2.1.4.2



QUESTIONS ?

Fire Alarm System Testing Requirement

- 1999 NFPA 72
- 2000 NFPA 101
- 2007 MN State Fire Code (MSFC)



Maintenance, Inspection and Testing

- The building owner **shall** be responsible for ensuring that the fire and life safety systems are maintained in an operable condition at all times.

– MSFC 907.20.5 & NFPA 72 7-1.2

Annual Testing

- Service Personnel
 - Shall be qualified and experienced in testing, inspection and maintenance of the fire alarm system
 - Factory trained or certified
 - NICET Certified
 - Certified by state or local authority
 - NFPA 72 7-1.2.2
 - MSFC 907.20.5

Initial Acceptance Testing

- NFPA 72 7-1.6.1 & MSFC 907.17
 - All new systems shall be inspected and tested in accordance with the requirements of Chapter 7.
 - Record of completion need to be filled out by contractor (Figure 1-6.2.1 & MSFC 907.18)
 - Kept on file for life of the building

Reacceptance Testing

- NFPA 72 7-1.6.2
 - Added or deleted system components
 - Any modifications, repairs, or adjustment to system hardware or wiring
 - Any changes to site-specific software
 - Kept on file till next reacceptance test

Annual Testing

- Documentation
 - 2 years worth of data in Life Safety Documentation book (NFPA 72 7-5.2)
 - 3 years on file per MSFC 901.6.2

Annual Testing

- Annual testing – needs to be done within a 365 day period
 - NFPA 101 – 9.6.14
 - NFPA 72 – Chapter 7
 - MSFC – 901.6

Annual Testing

- Devices
 - Manual pull stations
 - Smoke detectors
 - Heat detectors
 - Duct detectors
 - Tamper / Flow switches
 - Beam Detectors
 - Flames Detectors
 - Electromechanical releasing devices

Annual Testing

- Notification Appliances

- Horn or Chimes

- Horns or chimes need to be 15db above ambient sound level – measured 5 feet above floor (NFPA 72 4-3.2.2)

- Strobes

- In sure they are working and if you can see more than 2 strobes in field of view, strobes need to be synchronized (NFPA 72 4-4.4.1.1 (4))

Annual Testing

- Detector Sensitivity testing
 - Need to be done within 1 year after installation and every alternate year thereafter. After the second required test, and all detectors has remained within listed calibration the length shall be extended out to a maximum of 5 years. You are required to kept records of all nuisance alarms.
(NFPA 72 7-3.2.1 & MSFC 907.20.3)

Annual Testing

- Detector Sensitivity testing
 - Keep the 2 cycles of testing in book until after the 5 year test. After the 5 year test you have to go back to every alternate year for two cycles then 5 years if all pass.
 - Documentation has to show the factory setting of each smoke detector
 - The high – low, with built in +/- of detector and calibrated testing device

Annual Testing

- Detector Sensitivity testing
 - Calibrated machine
 - Newer system reports can be run from control panel
 - Circuit pulses
 - NFPA 72 7-3.2.1 & MSFC 907.20.4

Annual Testing





- Batteries – All fire alarm equipment (main panel, extenders, dialers and transponders)
 - Need to have date on them
 - Need to be changed every 4 years regardless of condition or before if battery fails load test
 - Tested under load
 - NFPA 72 Table 7-3.2 (6d)



Questions ?

Fire Sprinkler System Testing Requirement

- 1999 NFPA 13
- 1998 NFPA 25
- 2000 NFPA 101
- 2007 MN State Fire Code (MSFC)



Weekly Testing

- Fire Pump (1998 NFPA 25 5-3.2)
 - Automatic start of jockey pump
 - Automatic start of fire pump run for no flow for 10 minutes
 - Check for proper packing gland

Quarterly Testing

- Flow alarm (1998 NFPA 25 2-3.3)
 - Remote inspector test – record time
- Standpipe
 - Check valves and caps in place
- Fire Department Connection (FDC)
 - Check to sure collar freely turns
 - Insure 3 feet clearance around FDC

Annual Testing (1998 NFPA 25 2-2)

- Qualified person – license contractor
- Visual inspection of sprinkler system
 - Check for proper coverage area
 - Check for corroded sprinkler heads
 - Check for lint build up on sprinkler head
 - Check sprinkler heads
 - Standard response – 50 years
 - Quick response – 20 years

Annual Testing

- Check for proper orientation of sprinkler head
- Intermixing of standard and quick response sprinklers in same smoke compartments
- Spare sprinkler heads / wrench
- Dry heads – 10 year (walk-in coolers, freezers)
- Main drain test

Annual Testing

- Fire pump (1998 NFPA 25 5-3.3)
 - Flow testing (Hose monster)
 - Churn – no flow
 - 100%
 - 150%
 - Controller readings – all the three above test
 - Amps
 - Volts

Annual Testing

- Dry system
 - Trip test
 - Full trip every three years
(1998 NFPA 25 9-4.4.2.2.1)
 - Partial trip test the other two years
(1998 NFPA 25 9-4.4.2.2.2)
 - Dry valve inspection yearly

5 year testing

- Gauges
 - Calibrate or replaces all gauges on fire sprinkler system (1998 NFPA 25 2-3.2)
 - Check valves – Internal Inspection (1998 NFPA 25 9-4.2.1)
 - System
 - Fire Department Connection
 - Standpipe – Flow test (1998 NFPA 25 3-3.1.1)

5 year testing

- Pressure Reducing valve (1998 NFPA 25 9-5.2.2)

QUESTIONS ?

Minnesota State Fire Marshal

<http://www.fire.state.mn.us>